| COMPONENTS | IMPEDANCE | Standard Lengths |
|------------------------------|------------------|---|
| REVERSE POLARITY SMA MALE | 50 OHM | |
| STANDARD TNC MALE RG316/U | 50 OHM 50 OHM | |
| RG310/U | 50 OFIN | -24 24" |
| | | -36 36" |
| | | <u>-48</u> <u>48"</u> |
| | | -60 60" |
| | | -XXX Custom Length in inches |
| REVERSE POLARITY SMA MALE | | ENGTH MEASURED FROM CONTACT .590Ø STANDARD TNC MALE |
| | | ### STH FLOOR, BUILDING 1, YONGFU SCIENCE AND TECHNOLOGY CENTER INDUSTRIAL PARK, NANZHA DISTRICT 5, HUMEN,523900, DONG GUAN, GUANGDONG, CHINA WEBSITE: www.ebeestock.com |
| | | 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES. 4. LENGTH TOLERANCE IS ± 1.5% OR ± 3/8", WHICHEVER IS GREATER. |