| COMPONENTS | IMPEDANCE | | Standard Lengths | | | |
|---|------------------|--|---|--------------------------------------|-------------------|---------|
| REVERSE POLARITY TNC MALE STANDARD TNC MALE | 50 OHM 50 OHM | | -12 | 12" | | |
| RG316/U | 50 OHM | | -24 | 24 24" | | |
| | | | -36 | 36" | | |
| | | | -48 | 48" | | |
| | | | -60 | 60" | | |
| | | | -XXX | Custon | n Length in ir | nches |
| | | | | | | |
| .590ø REVERSE PO | | LENGTH MEASURED FROM CONTACT TO CONTACT | | STANDARD TNC MALE | | |
| | | CENTE | 8TH FLOOR, BUILDING 1, YONGFU SCIENCE AND TECHNOLOGY CENTER INDUSTRIAL PARK, NANZHA DISTRICT 5, HUMEN,523900,DONGGUAN, GUANGDONG, CHINA | | | |
| | | ebeestock ESTABLISHED 2003 | | E: www.ebees sales@ebees COAXI | | cs |
| | | DWG TITLE ET34518 | CABLE AGGLINDET, ROOTING, REVERGE | | | |
| | | SIZE A FSCM NO. 53919 | CAD FIL | E 022207 | SCALE N/A | 127 |
| | | NOTES: 1. UNLESS OTHERWISE SPECIFIEI 2. ALL SPECIFICATIONS ARE SUB. 3. DIMENSIONS ARE IN INCHES. 4. LENGTH TOLERANCE IS ± 1.5% | ЈЕСТ ТО СН | ANGE WITH | OUT NOTICE AT ANY | / TIME. |