| COMPONENTS | IMPEDANCE | |
|----------------------------------|-----------|--|
| REVERSE POLARITY TNC MALE | 50 OHM | Standard Lengths |
| STANDARD SMA MALE | 50 OHM | -12 12" |
| RG178B/U | 50 OHM | -24 24" |
| | | -36 36" |
| | | -48 48" |
| | | -60 60" |
| | | -XXX Custom Length in inches |
| | | |
| .590Ø REVERSE POLARITY TNC MALE | | LENGTH MEASURED FROM CONTACT STANDARD SMA MALE STH FLOOR, BUILDING 1, YONGFU SCIENCE AND TECHNOLOGY |
| | | CENTER INDUSTRIAL PARK, NANZHA DISTRICT 5, Humen,523900, dong guan, guangdong, china |
| | | ESTABLISHED 2003 WEBSITE: www.ebeestock.com EMAIL: sales@ebeestock.com COAXIAL & FIBER OPTICS |
| | | DWG TITLE ET34531 DES. CABLE ASSEMBLY, RG178B/U, REVERSE POLARITY TNC MALE TO STANDARD SMA MALE (LEAD FREE) |
| | | REV. A FSCM NO. 53919 CAD FILE 020608 SCALE N/A SIZE A 147 |
| | | NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES. 4. LENGTH TOLERANCE IS ± 1.5% OR ± 3/8", WHICHEVER IS GREATER. |