COMPONENTS	IMPEDANCE	Standard Lengths	
REVERSE POLARITY TNC MALE STANDARD SMA MALE	50 OHM	-12 12"	
RG400/U	50 OHM 50 OHM	-24 24"	
	V	-36 36"	
		-48 48"	
		-60 60"	
		-XXX Custom Length in inch	165
		7600 Gustom Length in mon	100
,590¢  REVERSE POLYTING MALE		ENGTH MEASURED FROM CONTACT TO CONTACT  STANDARD SMA MALE	
		### \$TH FLOOR, BUILDING 1, YONGFU SCIENCE AND TECHNOLO  CENTER INDUSTRIAL PARK, NANZHA DISTRICT 5,  HUMEN,523900,DONG GUAN, GUANGDONG, CHINA	JGY
		WEBSITE: www.ebeestock.com EMAIL: sales@ebeestock.com COAXIAL & FIBER OPTICS	i
		DWG TITLE  ET34557  DES. CABLE ASSEMBLY, RG400/U, REVERSE POLARITY TNC MALE TO STANDARD SM MALE (LEAD FREE)	
		REV. A FSCM NO. 53919 CAD FILE 020608 SCALE N/A SIZE A	147
		NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME 3. DIMENSIONS ARE IN INCHES. 4. LENGTH TOLERANCE IS ± 1.5% OR ± 3/8", WHICHEVER IS GREATER.	E.