COMPONENTS	IMPEDANCE			Standard Lengths		
SSMB PLUG	50 OHM		-6	6"	T	
UMCX PLUG RG178B/U	50 OHM 50 OHM		-12	12"		
KOTTODIO	JO OTHER		-18	18"		
			-xx	to c	nches	
				(24" Max Length)		
	X					
90ees	VC,					
,	Ç					
C) [~]					
100	I	LENGTH MEASURED	FROM I			
		CONTACT TO CON	TACT			
			A -			
		((√ ^			
				1		
0.19		//				
ø [4.7]						
	SSMB		UM	CV.		
	PLUG		PLU			
		.09				
	.16 [4.0]	[2.3]		i 1, YONGFU SCIENCE AND TECHI Trial Park, Nanzha district (_	
	[1.0]	•		DONG GUAN, GUANGDONG, CHIN		
				BITE: www.ebeestock.com L: sales@ebeestock.com COAXIAL & FIBER OP1	rics	
		<u> </u>	DWG TITLE DES. CABLE ASSEMBLY, RG178B/U, SSMB PLUG		MB PLUG	
		I	ET34947	TO UMCX PLUG		
	View A		REV FSCM NO. 53919 CAD	FILE 082411 SCALE N/A SI	ZE A 2231	
			NOTALESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm]. 4. LENGTH TOLERANCE IS ± 1.5% OR ±3/8", WHICHEVER IS GREATER.			