| 5-                  |           |                      | -                               | 5  |
|---------------------|-----------|----------------------|---------------------------------|--|
| COMPONENTS          | IMPEDANCE |                      |                                 | Standard Lengths   |
| UMCX PLUG           | 50 OHM    |                      | -6                              | 6"   |
| SMA FEMALE BULKHEAD | 50 OHM    |                      | <u> </u>                        |  |
| RG178B/U            | 50 OHM    |                      | -12                             | 12"  |
|                     | 1         |                      | -18                             | 18"  |
|                     |           |                      | -XXX                            | Custom Length in inches  |
|                     |           |                      |                                 | (24" Max Length)   |
|                     |           |                      |                                 |  |
|                     |           |                      |                                 |  |
|                     |           |                      | 1/4                             | -36 UNS-2A   |
| UMCX<br>PLUG        |           | LENGTH MEASURED FROM | MC                              | 0.24<br>[6.0]<br>+<br>0.25<br>Ø [6.4]  |
| .16 [4.0]           |           | ( CE                 | R, BUILDING 1,<br>NTER INDUSTRI | YONGFU SCIENCE AND TECHNOLOGY<br>AL PARK, NANZHA DISTRICT 5,<br>NGGUAN, GUANGDONG, CHINA |
| H                   |           | )                    |                                 | - www.cheestook.com  |

.09 [2.3]

View A

WEBSITE: www.ebeestock.com EMAIL: sales@ebeestock.com COAXIAL & FIBER OPTICS ESTABLISHED 2003 **DWG TITLE** CABLE ASSEMBLY, RG178B/U, UMCX PLUG TO SMA FEMALE BULKHEAD ET34958 **FSCM NO. 53919** CAD FILE 082411 SCALE N/A SIZE A 2231 REV. -NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].
4. LENGTH TOLERANCE IS ± 1.5% OR 3/8", WHICHEVER IS GREATER.