| COMPONENTS | IMPEDANCE | | | 1 | Stor | dard Langth | - |
|---------------------------|-----------|----------|---|--|---|------------------|---------|
| SMA MALE RIGHT ANGLE | 50 OHM | | | | | dard Length | 5 |
| SMA MALE RIGHT ANGLE | 50 OHM | | | -12 | 12" | | |
| | | | | -24 | 24" | | |
| | | | | -36 | 36" | | |
| | | | | -48 | 48" | | |
| | | | | -60 | 60" | | |
| | | | | -xx | Custon | n Length in i | nches |
| | | | | | j. | | |
| SMA MALE RIGHT ANGL | E | | STH FLOOR, BL CENTER | IILDING 1, IILDING 1, INDUSTRI 523900,DO WEBSITI EMAIL: | AL PARK, N/ NGGUAN, G E: www.ebees sales@ebees COAX | | À |
| | | E | T35228 | | | O SMA MALE RIGHT | ANGLE |
| | | SIZ | E A FSCM NO. 53919 | CAD FIL | E 021307 | SCALE N/A | 127 |
| | | 2. 3. | TES: UNLESS OTHERWISE SPECIFIED ALL SPECIFICATIONS ARE SUBJI DIMENSIONS ARE IN INCHES. LENGTH TOLERANCE IS ± 1.5% O | ЕСТ ТО СН | | OUT NOTICE AT AN | Y TIME. |