


| COMPONENTS | IMPEDANCE |
|------------|-----------|
| SMA MALE | 50 OHM |
| TNC MALE | 50 OHM |
| RG316/U | 50 OHM |

| Standard Lengths | |
|------------------|-------------------------|
| -12 | 12" |
| -24 | 24" |
| -36 | 36" |
| -48 | 48" |
| -60 | 60" |
| -xx | Custom Length in inches |



| | | | | |
|---|-----------------------|---|------------------|------------|
|  8TH FLOOR, BUILDING 1, YONGFU SCIENCE AND TECHNOLOGY CENTER INDUSTRIAL PARK, NANZHA DISTRICT 5, HUMEN, 523900, DONGGUAN, GUANGDONG, CHINA WEBSITE: www.ebeestock.com EMAIL: sales@ebeestock.com ESTABLISHED 2003 COAXIAL & FIBER OPTICS | | | | |
| DWG TITLE ET35305 | | DES. CABLE ASSEMBLY, RG316/U, SMA MALE TO TNC MALE | | |
| SIZE A | FSCM NO. 53919 | CAD FILE 021307 | SCALE N/A | 127 |
| NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES. 4. LENGTH TOLERANCE IS ± 1.5% OR ±3/8", WHICHEVER IS GREATER. | | | | |