COMPONENTS	IMPEDANCE			Standard Laugtha	
SMA FEMALE BULKHEAD	50 OHM			10	Standard Lengths
SMA FEMALE BULKHEAD	50 OHM			-12	12"
RG316/U	50 OHM			-24	24"
				-36	36"
				-48	48"
				-60	60"
				-XXX	Custom Length in inches
	LEN	IGTH MEASURED FROM			
	C	CONTACT TO CONTACT	6		
		Í	0.45		
		-	[11,5]		
		0.05			
		[1,2]	1		
		5/16	0.24		
		HEX ——	[6.0]		
		/ / ·			
			· · ·	(+	'
			Щ	(1	
			l .	C	0.25
SMA FEMALE		.140 [3.6]	-1/4-36 UNS-2A	Г	 6.4]
BULKHEAD		MAX —	—	_	
		PANEL	MC	OUNTIN	IG HOLE
		.140 [3.6] MAX PANEL			
		FEMALE BULKHEA	D		
	0	T			
					YONGFU SCIENCE AND TECHNOLOGY Il Park, nanzha district 5,
			HUMEN,52	23900, DO N	IGGUAN, GUANGDONG, CHINA
			ebeestock		: www.ebeestock.com ales@ebeestock.com
			ESTABLISHED 2003	Luril. 3	COAXIAL & FIBER OPTICS
			DWG TITLE	DES.	CABLE ASSEMBLY, RG316/U, SMA FEMALE
			ET35475	'	BULKHEAD TO SMA FEMALE BULKHEAD
			REV. B FSCM NO. 53919	CAD FIL	E 082411 SCALE N/A SIZE A 2231
				ALL DIMEN	SIONS ARE NOMINAL. ANGE WITHOUT NOTICE AT ANY TIME.
			3. DIMENSIONS ARE IN INCHES [mm]	l.	
			I. LENGTH TOLERANCE IS ± 1.5% OF	R 3/8", WHI	CHEVER IS GREATER.