| 2011201121 | | | | |
|-------------------------------|------------------|---|---------------------------------------|--|
| COMPONENTS | IMPEDANCE | Standard Lengths | | |
| SMA MALE SMA MALE RIGHT ANGLE | 50 OHM 50 OHM | -12 12" | · · · · · · · · · · · · · · · · · · · | |
| RG58C/U | 50 OHM | -24 24" | T i | |
| | | -36 36" | | |
| | | -48 48" | | |
| | | -60 60" | | |
| | | -XXX Custom Length in | inches | |
| | | | | |
| .312 HEX | | LENGTH MEASURED FROM CONTACT CONTACT TO CONTACT .612 | | |
| | SMA MALE | SMA MALE RIGHT ANGLE | | |
| | | STH FLOOR, BUILDING 1, YONGFU SCIENCE AND TECH CENTER INDUSTRIAL PARK, NANZHA DISTRICT Humen,523900, do ng guan, guangdo ng, chi | Г 5, | |
| | | ebeestock ESTABLISHED 2003 WEBSITE: www.ebeestock.com EMAIL: sales@ebeestock.com COAXIAL & FIBER O | PTICS | |
| | | DES. CABLE ASSEMBLY, RG58C/U, SI TO SMA MALE RIGHT ANGLE | MA MALE | |
| | | | SIZE A 147 | |
| | | NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT A 3. DIMENSIONS ARE IN INCHES. 4. LENGTH TOLERANCE IS ± 1.5% OR ±3/8", WHICHEVER IS GREATER. | NY TIME. | |