| COMPONENTS | IMPEDANCE | | |
|----------------------|-----------|--|---------------------------------------|
| SMA MALE | 50 OHM | Standard Lengt | ths |
| SMA MALE RIGHT ANGLE | 50 OHM | -12 12" | |
| RG316-DS | 50 OHM | -24 24" | |
| | | -36 36" | |
| | | <u>-48</u> <u>48"</u> | |
| | | <u>-60</u> 60" | |
| | | -XXX Custom Length in | ı inches |
| | | | |
| .312 HEX SMA MALE | | SMA MALE RIGHT ANGLE STH FLOOR, BUILDING 1, YONGFU SCIENCE AND TEC CENTER INDUSTRAL PARK, NANZHA DISTRICT HUMEN, 52390, DONG GUAN, GUANGEONG, CH WEBSITE: WWW.ebbestock.com COAXIAL & FIBER OI DWG TITLE ET35634 DES. CABLE ASSEMBLY, RG316-DS, S TO SMA MALE RIGHT ANGLE (LE REV. A FSCM NO. 53919 CAD FILE 021308 CALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT AI 3. DIMENSIONS ARE IN INCHES. 4. LENGTH TOLERANCE IS 21.5% OR ±3/8", WHICHEVER IS GREATER. | OPTICS SMA MALE LEAD FREE) SIZE A 147 |