COMPONENTS	IMPEDANCE		Standard Lengths
SMA FEMALE BULKHEAD	50 OHM	-12	12"
MA FEMALE BULKHEAD RG402/U	50 OHM 50 OHM	-24	24"
(G-102/G	30 OTHE		
		-36	36"
		-48	48"
		-60	60"
		-xxx	Custom Length in inches
.438 HEX	LENGTH MEASURED FROMCONTACT TO CONTACT .085 .135 MAX	.415 250-36 UNS-2A	+) .250
BULKHEAD	FI	SMA EMALE LKHEAD	MOUNTING HOLE

CENTER INDUSTRIAL PARK, NANZHA DISTRICT 5, HUMEN,523900, DONG GUAN, GUANGDONG, CHINA WEBSITE: www.ebeestock.com ebeestock EMAIL: sales@ebeestock.com ESTABLISHED 2003

COAXIAL & FIBER OPTICS DES. CABLE ASSEMBLY, RG402/U, SMA FEMALE

BULKHEAD TO SMA FEMALE BULKHEAD

SCALE N/A

DWG TITLE ET35704 REV. A FSCM NO. 53919

CAD FILE 012408

SIZE A 147

NOTES:

- UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 DIMENSIONS ARE IN INCHES.
- 4. LENGTH TOLERANCE IS ± 1.5% OR ± 3/8", WHICHEVER IS GREATER.