COMPONENTS	IMPEDANCE		Standard Lengths		
SMA FEMALE BULKHEAD	50 OHM		-12	12"	
SMA FEMALE BULKHEAD RG402/U	50 OHM 50 OHM		-24	24"	
NO 10210			-36	36"	
			-		
			-48	48"	
			-60	60"	
			-XXX	Custom Length in inches	
.438 HEX SMA FEMALE BULKHEAD	LENGTH MEASURED IN CONTACT TO CONT			+ .250 MOUNTING HOLE	
		CE NTER	INDUSTRA 523900,DOI Website	YONGFU SCIENCE AND TECHNOLOGY AL PARK, NANZHA DISTRICT 5, NGGUAN, GUANGDONG, CHINA :: www.ebeestock.com ales@ebeestock.com COAXIAL & FIBER OPTICS	
		DWG TITLE ET35707	DES. (CABLE ASSEMBLY, RG402/U, SMA FEMALE BULKHEAD TO SMA FEMALE BULKHEAD	

REV. A FSCM NO. 53919

CAD FILE 012408

NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.

2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.

3. DIMENSIONS ARE IN INCHES.

4. LENGTH TOLERANCE IS ± 1.5% OR ± 3/8", WHICHEVER IS GREATER.

SCALE N/A

SIZE A 147