| COMPONENTS                               | IMPEDANCE                               |      | Standard Lengths                                     |
|--|---|------|--|
| MA FEMALE BULKHEAD<br>MA FEMALE BULKHEAD | 50 OHM<br>50 OHM                        | -12  | 12"  |
| G402/U                                   | 50 OHM 50 OHM                           | -24  | 24"  |
|  |   | -36  | 36"  |
|  |   | -48  | 48"  |
|  |   |      | <del> </del>   |
|  |   | -60  | 60"  |
|  |   | -XXX | Custom Length in inches                              |
| .438 HEX  SMA FEMALE BULKHEAD            | LENGTH MEASURED FROM CONTACT TO CONTACT |      | + .250  MOUNTING HOLE  YONGFU SCIENCE AND TECHNOLOGY |

**ebeestock** WEBSITE: www.ebeestock.com EMAIL: sales@ebeestock.com ESTABLISHED 2003

**COAXIAL & FIBER OPTICS** 

DES. CABLE ASSEMBLY, RG402/U, SMA FEMALE BULKHEAD TO SMA FEMALE BULKHEAD

DWG TITLE ET35708

REV. A FSCM NO. 53919

CAD FILE 012408

SCALE N/A SIZE A 147

NOTES:

- UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
   ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
   DIMENSIONS ARE IN INCHES.
- 4. LENGTH TOLERANCE IS ± 1.5% OR ± 3/8", WHICHEVER IS GREATER.