COMPONENTS	IMPEDANCE					1	Star	ndard Leng	gths	
SMA FEMALE BULKHEAD SMA FEMALE BULKHEAD	50 OHM 50 OHM					-12	12"			
						-24	24"			
						-36	36"			
						-48	48"			
						-60	60"			
						-XXX	Custo	m Length i	n inche	es
.438 HEX SMA FEMALE BULKHEAD		EASURED FROM	.085—• .135 MAX PANEL	SMA FEMALE BULKHEAD		NIIII DING 1		.235 .250 ING HOLE	CHNUI UG	2V
					CE NTE	R INDUSTR	IAL PARK, N	ANZHA DISTRI Uangdong, C	CT 5,	
				eb	eestock established 2003		E: www.ebee sales@ebees COAX		OPTICS	
					<u> ET35916</u>			CABLE ASSEMI KHEAD TO SMA I		
					FSCM NO. 53919	CAD FIL	E 012408	SCALE N/A	SIZE A	147
				2. ALL S 3. DIME	SS OTHERWISE SPECIFIED PECIFICATIONS ARE SUB ISIONS ARE IN INCHES. TH TOLERANCE IS ± 1.5%	ЈЕСТ ТО СН	ANGE WITH	OUT NOTICE AT	ANY TIME	<u>.</u>