COMPONENTS		Standard Lengths
SMA MALE SMA FEMALE	50 OHM 50 OHM	-12 12"
RG62A/U	93 OHM	-24 24"
		-36 36"
		-48 48"
		-60 60"
		-XXX Custom Length in inches
.312 HEX		LENGTH MEASURED FROM CONTACT TO CONTACT .312 HEX
	SMA MALE	.250-36 UNS-2A
		8TH FLOOR, BUILDING 1, YONGFU SCIENCE AND TECHNOLOGY CENTER INDUSTRIAL PARK, NANZHA DISTRICT 5, HUMEN,523900,DONGGUAN, GUANGDONG, CHINA
		ebeestock WEBSITE: www.ebeestock.com ESTABLISHED 2003 EMAIL: sales@ebeestock.com
		DWG TITLE ET36023 DES. CABLE ASSEMBLY, RG62A/U, SMA MALE TO SMA FEMALE
		REV. AFSCM NO. 53919CAD FILE021308SCALE N/ASIZE A147NOTES:1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.3. DIMENSIONS ARE IN INCHES.4. LENGTH TOLERANCE IS ± 1.5% OR ±3/8", WHICHEVER IS GREATER.