COMPONENTS	IMPEDANCE					Star	ndard Leng	jths
SMA FEMALE BULKHEAD SMA FEMALE BULKHEAD	50 OHM 50 OHM				-12	12"		
					-24	24"		
					-36	36"		
					-48	48"		
					-60	60"		
					-XXX	Custor	m Length i	n inches
.438 HEX SMA FEMALE BULKHEAD		I MEASURED FROTACT TO CONTAC	.085 —► .135 MAX PANEL	SMA FEMALE ULKHEAD	RIJII DING 1		.235 .250 ING HOLE	CHNOLOGY
	14			CEN	TER INDUSTR	KIAL PARK, N	IANZHA DISTRI Guangdong, C	CT 5,
				ebeestock ESTABLISHED 2003		E: www.ebee sales@ebee COAX		OPTICS
				DWG TITLE ET36059			CABLE ASSEME KHEAD TO SMA I	
				REV. A FSCM NO. 5391	CAD FIL	E 012408	SCALE N/A	SIZE A 147
				NOTES: 1. UNLESS OTHERWISE SPECIF 2. ALL SPECIFICATIONS ARE SU 3. DIMENSIONS ARE IN INCHES. 4. LENGTH TOLERANCE IS ± 1.5	ВЈЕСТ ТО СН	ANGE WITH	OUT NOTICE AT	ANY TIME.