COMPONENTS	IMPEDANCE						Stand	dard Leng	ıths
SMA FEMALE BULKHEAD SMA FEMALE BULKHEAD	50 OHM 50 OHM					-12	12"		
	00 011111					-24	24"		
						-36	36"		
						-48	48"		
						-60	60"		
						-XXX	Custom	ı Length i	n inches
.438 HEX SMA FEMALE BULKHEAD		EASURED FROM	.135 MAXPANEL	SMA				.235 .250 MG HOLE	
	No.					RINDUSTR	IAL PARK, NA	IENCE AND TE Inzha distri Jangdong, C	CT 5,
				eb	eestock ESTABLISHED 2003		E: www.ebees sales@ebeest COAXI		OPTICS
				DES. CABLE ASSEMBLY, SMA FEMALE BULKHEAD TO SMA FEMALE BULKHEAD (LEAD FREE)					
				REV. A	FSCM NO. 53919	CAD FIL	E 012408	SCALE N/A	SIZE A 147
			1	2. ALL S 3. DIME	SS OTHERWISE SPECIFIED PECIFICATIONS ARE SUBJ ISIONS ARE IN INCHES. TH TOLERANCE IS ± 1.5% C	ECT TO CH	ANGE WITHOU	UT NOTICE AT	ANY TIME.