COMPONENTS	IMPEDANCE						Stan	dard Leng	yths	
SMA FEMALE BULKHEAD SMA FEMALE BULKHEAD	50 OHM 50 OHM					-12	12"			
						-24	24"			
						-36	36"			
						-48	48"			
						-60	60"			
						-XXX	Custon	n Length i	n inche	es
.438 HEX SMA FEMALE BULKHEAD		MEASURED FROM	.085	SMA EMALE LKHEAD	250-36 UNS-2A	EUIL DING 1		.235 .250 NG HOLE	CHNOLOG	GY .
	100				CE NTE	R INDUSTR	IAL PARK, N.	ANZHA DISTRI Uangdong, C	CT 5,	
					eestock established 2003			tock.com IAL & FIBER		
			4	DES. CABLE ASSEMBLY, SMA FEMALE BULKHEAD TO SMA FEMALE BULKHEAD (LEAD FREE)						
					FSCM NO. 53919	CAD FIL	E 012408	SCALE N/A	SIZE A	147
				2. ALL SI 3. DIMEN	S OTHERWISE SPECIFIED PECIFICATIONS ARE SUB- SIONS ARE IN INCHES. I'H TOLERANCE IS ± 1.5%	ЕСТ ТО СН	ANGE WITHO	OUT NOTICE AT	ANY TIME.	