COMPONENTS	IMPEDANCE				Ĩ	Stan	dard Leng	ths	
SMA MALE RIGHT ANGLE SMA FEMALE BULKHEAD	50 OHM 50 OHM				-12	12"			
RG196A/U	50 OHM				-24	24"			
					-36	36"			
					-48	48"			
					-60	60"			
					-XXX	Custon	n Length i	n inch	es
.612 .612 .612 .612 .612 .612 .612 .612	C ■ ●312 HEX	STH MEASURED FROM DNTACT TO CONTACT		ND			235 .250 .250		GY
	~ X			8TH FLOOR, BUILDING 1, YONGFU SCIENCE AND TECHNOLOGY CENTER INDUSTRIAL PARK, NANZHA DISTRICT 5, HUMEN,523900, DONGGUAN, GUANGDONG, CHINA					
			e	ESTABLISHED 2003		E: www.ebees sales@ebees COAX		OPTICS	
			DWG TI	ET36145			IBLY, RG196A/U, TO SMA FEMALI		
	100		REV. A	FSCM NO. 53919	CAD FIL	E 012508	SCALE N/A	SIZE A	147
			2. ALL 3. DIM	ESS OTHERWISE SPECIFIED A SPECIFICATIONS ARE SUBJE ENSIONS ARE IN INCHES. GTH TOLERANCE IS ± 1.5% OI	CT TO CH	ANGE WITHO	OUT NOTICE AT	ANY TIME	