


| MATERIALS | IMPEDANCE |
|-------------------------|-----------|
| REVERSE THREAD SMA MALE | 50 OHM |
| STANDARD SMA MALE | 50 OHM |
| | |
| | |

| Standard Lengths | |
|------------------|-------------------------|
| -12 | 12" |
| -24 | 24" |
| -36 | 36" |
| -48 | 48" |
| -60 | 60" |
| -XXX | Custom Length in inches |
| | |



| | | | | |
|--|--|-----------------|-----------|-----|
|  <p>8TH FLOOR, BUILDING 1, YONGFU SCIENCE AND TECHNOLOGY CENTER INDUSTRIAL PARK, NANZHA DISTRICT 5, HUMEN, 523900, DONG GUAN, GUANGDONG, CHINA</p> <p>WEBSITE: www.ebeestock.com EMAIL: sales@ebeestock.com</p> | | | | |
| ET36819 | DES. CABLE ASSEMBLY, RG223/U, REVERSE THREAD SMA MALE TO STANDARD SMA MALE | | | |
| SIZE A | FSCM NO. 53919 | CAD FILE 040207 | SCALE N/A | 127 |

- NOTES:**
- UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 - ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 - DIMENSIONS ARE IN INCHES.
 - LENGTH TOLERANCE IS $\pm 1.5\%$ OR $\pm 3/8"$, WHICHEVER IS GREATER.