COMPONENTS IMPEDANCE Standard		
REVERSE THREAD SMA MALE 50 OHM	Standard Lengths	
STANDARD SMA MALE 50 OHM -12 12"	-	
-24 24"	T T	
-36 36"		
-48 48"		
-60 60"		
-XXX Custom Lei	ngth in inches	
y <u></u>		
LENGTH MEASURED FROM		
CONTACT TO CONTACT		
.312 HEX 1		
REVERSE THREAD STANDARD SMA MALE SMA MALE		
REVERSE THREAD SMA MALE SMA MALE SMA MALE		
OHA HALL		
8TH FLOOR, BUILDING 1, YONGFU SCIENCE AND TECHNOLOGY		
CENTER INDUSTRIAL PARK, NANZHA DISTRICT 5, HUMEN,523900, DO NG GUAN, GUANGDO NG, CHINA		
ebeestock WEBSITE: www.ebeestock.co		
DES. CABLE ASSEMBLY, R	RG316/II REVERSE	
ET36831 Des. Cable assembly, in thread SMA MALE		

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES.
4. LENGTH TOLERANCE IS ± 1.5% OR ± 3/8", WHICHEVER IS GREATER.

CAD FILE 020608

SIZE A 147

SCALE N/A

REV. A FSCM NO. 53919